

Elgood Industrial Flooring



Unit 29, Mulberry Court, Bourne Industrial Park
Crayford, Kent DA1 4BF
Tel 01322 552 030 Fax 01322 552 033
Email admin@elgood.com

Cleaning of Elgood Britdura Solvent Free Epoxy Flooring.

Maintenance and Cleaning.

We recommend that the floor is not cleaned for at least a week following the installation.

The floor can be routinely washed with water or an alkaline detergent cleaning solution designed for use in scrubber dryer machines. These products should be used according to the manufacturers instructions. Typical instructions are 1 to 10 parts hot water in isolated heavily soiled areas and 1 to 80 parts water when used in scrubber dryer machines.

Recommended Product: **Elgood Epoxy Floor Cleaning Detergent**

We are happy to supply this product direct to you.

Citrus based degreasing and cleaning liquids should not be used on Epoxy floorings due to the presence of solvents that temporarily affect the surface of the floor.

Detergent based degreasing products should also not be used to clean the floor due to the presence of solvent.

If you have any doubts about the cleaning liquid you intend using, then we would be pleased to investigate the product for you.

Cleaning Methods.

Ideally, the floor should be maintained by mechanical scrubbing machines using preferably soft nylon brushes or pads.

For routine cleaning with a scrubber dryer machine, we recommend that the cleaning solution is diluted 1 part to 80 parts water when poured into the machine.

Steam Cleaning should not be used.

A typical procedure for heavy soiling is as follows:

1. Pour diluted measure of cleaning solution onto the floor surface and leave for 5 minutes.
2. **Scrub** clean the floor with bristle brushes without collecting the liquid away from the floor.
3. Leave the scrubbed solution on the floor for **fifteen minutes** so that it can continue to break down the mark / soiling.
4. The floor can then be scrubbed for a **second** time.
5. Use a wet vacuum or scrubbing machine with a collection facility to clean the surface of the floor of any residue and to help prevent the occurrence of tide marks.

Maintenance.

In the event of damage and / or repair work being required for the floor, please contact:01322 552030

Quality Floorings - Professionally Installed

Elgood Industrial Flooring Limited. Registered in England Number 2399454

www.elgood.com